

## BARCODE VERIFIER MODEL SELECTION GUIDE

Model #	Windows compatible	MAC compatible	Technology	Wavelength	Continuous Scanning?	Interface	Linear/2D	Field Of View	Resolution	Connect to PV1000?
6015	yes	yes	CCD	red, 660nm	no	USB, RS232 optional	linear	68 mm	3, 5, 6, 10, 20 mil	yes
6515	yes	yes	CCD	red, 660nm	no	USB, RS232 optional	linear	125 mm	5, 6, 10, 20 mil	yes
7015	yes	yes	CCD	red, 660nm	no	USB, RS232 optional	linear	195 mm	8, 10, 20 mil	yes
6025 S	yes	no	CCD	red, 660nm	yes	USB2	linear	68 mm	3, 5, 6, 10, 20 mil	no
6525 S	yes	no	CCD	red, 660nm	yes	USB2	linear	125 mm	5, 6, 10, 20 mil	no
7025 S	yes	no	CCD	red, 660nm	yes	USB2	linear	195 mm	8, 10, 20 mil	no
PV 1072	n/a	n/a	CCD	red, 660nm	no	USB	linear	68 mm	3, 5, 6, 10, 20 mil	n/a
6000 W	yes	no	CCD	white light	no	USB, RS232 optional	Pharmacode only	68 mm	n/a	no
12000	yes	no	Camera	red, 660nm	n/a	USB2	2D	25 x 18 mm	3 mil and more, in steps of 1 mil	no
12500	yes	no	Camera	red, 660nm	n/a	USB2	2D	38 x 26 mm	3 mil and more, in steps of 1 mil	no
12800	yes	no	Camera	red, 660nm	n/a	USB2	2D	25 x 18 mm	3 mil and more, in steps of 1 mil	no